PROFISHARK 10G

IN-DEPTH COPPER AND FIBER NETWORK TROUBLESHOOTING

COMPREHENSIVE 1G/10G COPPER AND FIBER FIELD TESTING & MONITORING

The ProfiShark 10G is the perfect tool for the field engineer as well as for long-term traffic collection. Easy to use and pocket-sized, this portable device gives you all the flexibility and performance you require for network monitoring.

Combine the ProfiShark 10G with a Windows, Linux or macOS computer through its USB 3.0 port for a complete network analysis solution. The ProfiShark 10G captures packets of all sizes and types and offers a wide assortment of hardware filters, statistics, and capture and configuration options, through the ProfiShark Manager.

FEATURES

▷ 1G/10G monitoring on USB 3.0
▷ 1G, 10G, copper and fiber SFPs compatible
▷ USB 3.0 powered
▷ Hardware aggregation
▷ SPAN and In-Line modes
▷ Hardware filtering, deep packet inspection
▷ Packet slicing
▷ 5 ns hardware timestamp
▷ Customizable real-time statistics
▷ In-depth network port diagnostics
▷ Low level error and bandwidth monitoring
▷ Direct capture to disk
▷ Invisible to the network

LONG-TERM TRAFFIC CAPTURE

The long-term capture feature is designed to help you catch intermittent problems in the act. By connecting a NAS to the ProfiShark, captures can be done for long periods of time. Included in ProfiShark software package.

▷ Ringbuffer or normal capture mode
▷ Split capture to different files, based on time or size
▷ Compatible with all Intel-based Synology NAS systems

TECHNICAL SPECIFICATIONS

CONNECTORS	ACCESSORIES
2 x SFP/SFP+ 1 x USB 3.0 1 x 5 VDC optional input	1.8 m USB 3.0 cable 1.5 m USB A male to DC 5V adapter USB key
DIMENSIONS (WxDxH)	**MAX. NETWORK LATENCY**
105 x 124 x 26 mm — 4.13 x 4.88 x 1.02 in	10 Gbps: 328 ns
WEIGHT	**SYSTEM REQUIREMENTS**
280 g — 0.62 lb	Dual Core Processor — 4 GB memory — USB 3.0 port
COMPLIANCE	**LEDS**
RoHS — CE	4 x Link/Activity — 1 x Power
SUPPORTED OS	
Windows 7 / 8 / 10 (32-bit & 64-bit) — Linux — macOS	

ORDER REFERENCE   C1AP-10G

PROFITAP

v3.6-11.21